

# China Retaliatory Tariffs

## Tariff Exclusions Granted

### Batch 1, List 3

Updated: 2/27/2020



In December 2019, China released another list of products exempted from additional Chinese tariffs.

List 2 exclusions are effective from September 17, 2019 to September 16, 2020. While these products are exempt from additional tariffs, they are not subject to refunds.

| HTS Code | Product Description (Chinese)   | Product Description (English)   |
|----------|---|---|
| 27101999 | 白油（液体烃类混合物组成的无色透明油状液体，由原油分馏所得。商品成分为100%白矿油，40℃时该产品粘度为65mm <sup>2</sup> /s，闪点为225℃，倾点为-10℃，比重（20℃/20℃）为0.885）                      | White oil (a colorless transparent oily liquid composed of a mixture of liquid hydrocarbons, obtained by fractional distillation of crude oil. The commercial composition is 100% white mineral oil, the viscosity of the product at 40 ° C is 65mm <sup>2</sup> / s, the flash point is 225 ° C and the pour point -10 , specific gravity (20 / 20 ) is 0.885) |
| 27129010 | 食品级微晶石蜡，相应指标符合《食品级微晶蜡》（GB22160-2008）的要求   | Food grade microcrystalline paraffin, the corresponding index meets the requirements of "Food grade microcrystalline wax" (GB22160-2008)  |
| 39012000 | 茂金属高密度聚乙烯，密度0.962g/cm <sup>3</sup> ，熔流率0.85g/10min  | Metallocene high-density polyethylene, density 0.962g / cm <sup>3</sup> , melt flow rate 0.85g / 10min  |
| 39014010 | 粘指剂（一种乙烯丙烯共聚物，成分为乙烯65%，丙烯35%，比重小于0.94）  | Finger-sticking agent (a copolymer of ethylene and propylene, composed of 65% ethylene, 35% propylene, and specific gravity less than 0.94)   |
| 39014020 | 线性低密度的乙烯与1-辛烃共聚物  | Linear low density copolymer of ethylene and 1-octane   |
| 39021000 | 共聚抗冲等级聚丙烯·熔融指数MI<0.5g/10min，UL认证黄卡中RTI（相当于长期工作温度）115，悬臂梁缺口冲击强度（测量方法ISO 180）：23 时为 64KJ/m <sup>2</sup> ，-40 时为4.0KJ/m <sup>2</sup> | Copolymer impact grade polypropylene, melt index MI <0.5g / 10min, UL certified yellow card RTI (equivalent to long-term operating temperature) 115 , cantilever beam notched impact strength (measurement method ISO 180): 64KJ / m <sup>2</sup> at 23 m, 2.4.0KJ / m <sup>2</sup> at -40  |